



Part Number: 9919

Hook- Up/ Lead Wire UL AWM Styles 1007 & 1569, (1) 20 AWG (7x28) TC, PVC, 300V RMS 80°C, 300V 105°C

Request Sample
Requ

Product Description

One 20 AWG stranded (7x28) tinned copper conductor, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor					
AWG	Stranding	Materi	al	No. of Conductors	No. of Pairs
20	7x28	TC - Tinned	Copper	1	6
Conductor Count:		1			
Conductor Size:		20 AW	G		

Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.069 in	0.016 in	0.015 in

Outer Jacket Material

Material No Jacket

Electrical Characteristics

Conductor DCR



Shielding: Unshielded

Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V	300 V

Other Electrical Characteristic 2: Return Loss tested in accordance with ASTM D 4566 - 05 paragraph 50.3, using a 75 Ohm fixed bridge and termination.

Temperature Range

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C

Mechanical Characteristics

Bulk Cable Weight:	5 lbs/1000ft
Min Bend Radius/Installation:	6 in

Standards

UL Rating:	300V RMS, 80°C and 300V, 105°C
UL AWM Style:	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
CSA Rating:	300V RMS, 90°C and 300V, 105°C
CSA AWM Specification:	TRSR-64
CSA Type:	TRSR-64
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Outdoor:	No

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

ım (Y/N): No	
--------------	--

Part Number

Variants

Item #	Color	Footnote
9919 010100	Black	
9919 0101000	Black	Р
9919 013100	Blue, Dark	
9919 0131000	Blue, Dark	Р
9919 001100	Brown	
9919 0011000	Brown	Р
9919 0081000	Gray	Р
9919 005100	Green, Dark	
9919 0051000	Green, Dark	Р
9919 0031000	Orange	Р
9919 002100	Red	
9919 0021000	Red	Р
9919 007100	Violet	
9919 0071000	Violet	Р
9919 009100	White	
9919 0091000	White	Р
9919 004100	Yellow	
9919 0041000	Yellow	Р

P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

© 2018 Belden, Inc

Footnote:

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.