



COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE

RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE) (2:1)




A-A





- NOTE 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
- 2. FOR MODIFICATION, ETC., PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
- 3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

1	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA: GOLD 0.1μm min. LEAD AREA: TIN-PLATING 1μm min. UNDER PLATING: NICKEL 1μm min.
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (COLD) CL					
DRAWN K. NAKAMURA		DESIGNED K. NAKAMURA		CHECKED K. Ogawa	
05.11.17		05.11.17		05.11.17	
APPROVED H. Okawa		APPROVED H. Okawa		RELEASED	
DRAWING NO. EDC3-150841-25			PART NO. FX8C-60P-SV2(71)		
SCALE 5 : 1			CODE NO. CL578-0541-3-71		
UNITS mm			1		



POLARIZATION MARK



TO
PCK