

USB Sync/Charge Cable with Apple 30-Pin Dock Connector, White, 3 ft. (1 m)

MODEL NUMBER: M110-003-WH



Charge and sync your Apple 30-pin iPhone, iPad or iPod using the USB port on your computer.

Description

The M110-003-WH USB Sync/Charge Cable connects your iPhone, iPad or iPod with the USB port on any computer, so you can charge your Apple device and transfer data. This 3-foot cable is MFi-certified for use with iPhone, iPad and iPod devices. It's compatible with iPhone (4s, 4, 3Gs, 3G and iPhone), iPad (3rd generation), iPad 2, iPad, iPod Touch (1st through 4th generation), iPod classic and iPod nano (1st through 6th generation).

Features

Syncs and Charges Your Apple 30-Pin Electronic Devices

- MFi-certified for use with iPhone, iPad and iPod devices
- Compatible with iPhone (4s, 4, 3Gs, 3G and iPhone), iPad (3rd generation), iPad 2, iPad, iPod Touch (1st through 4th generation), iPod classic and iPod nano (1st through 6th generation)

Compact and Convenient to Use

- Connects your 30-pin iPhone, iPad or iPod device and the USB port on your computer or wall charger
- Works with all computers

Specifications

OVERVIEW	
UPC Code	037332190062
Technology	Apple® 30-Pin Dock; USB (all versions)

Highlights

- Features an Apple-compatible 30-pin plug and a USB-A plug
- Works with any computer
- MFi-certified for use with iPhone, iPad and iPod devices
- Compatible with all Apple devices with 30-pin connectors

System Requirements

- USB-equipped computer or charger
- iPhone (4s, 4, 3Gs, 3G and iPhone), iPad (3rd generation), iPad 2, iPad, iPod Touch (1st through 4th generation), iPod classic and iPod nano (1st through 6th generation)

Package Includes

- M110-003-WH USB Sync/Charge Cable with Apple 30-Pin Dock Connector



INPUT	
Cable Length (ft.)	3
Cable Length (m)	1
PHYSICAL	
Wire Gauge (AWG)	24 Power Pair / 30 Data Pair
Shipping Dimensions (hwd / in.)	5.200 x 0.900 x 2.600
Shipping Dimensions (hwd / cm)	13.21 x 2.29 x 6.60
Shipping Weight (lbs.)	0.1000
Shipping Weight (kg)	0.05
Unit Packaging Type	Box
Material of Construction	PVC
Color	White
Cable Outer Diameter (OD)	2.8mm
Cable Jacket Rating	VW-1
ENVIRONMENTAL	
Operating Temperature Range	-4 to 140 F (-20 to 60 C)
Storage Temperature Range	-4 to 176 F (-20 to 80 C)
Relative Humidity	0% to 90% RH, Non-Condensing
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	30 PIN APPLE (MALE)
Connector Plating	Nickel
Contact Plating	Gold
FEATURES & SPECIFICATIONS	
USB Specification	USB 2.0 (up to 480 Mbps)
CERTIFICATIONS	
Certifications	Tested to MFI, CA65, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>