

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT 2003 BY TYCO ELECTRONICS CORPORATION. ALL INTERNATIONAL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
J	-	A	RELEASE	07JUN11	TQ SY

FEEDING DIRECTION

Dimensions: 1.75 ± 0.1 , $\phi 1.55 \pm 0.05$ (TYP.), 4 ± 0.1 (TYP.), 2 ± 0.1 , 24 ± 0.1 , 32 ± 0.3 , 14.2 , 160mm (MIN) EMPTY POCKET, CONNECTOR LOADED AREA, 100mm (MIN) EMPTY POCKET.

DETAIL A

NOTES :

- 10 POCKETS HOLE PITCH CUMULATIVE TOLERANCE $\pm 0.2\text{mm}$.
- NUMBER OF CONNECTORS : 230 PCS/REEL.
- COVER TAPE PEELING STRENGTH : $0.1 \sim 1.3\text{N}$. AT $300\text{mm}/\text{min}$.

FEEDING DIRECTION

Carrier tape dimensions: $\phi 100 \pm 0.5$, $\phi 330 \pm 2.0$.

Carrier tape detail: 0.20 , $R0.75$.

COVER TAPE

PEELING DIRECTION

CARRIER TAPE

FEEDING DIRECTION

Angle: $165^\circ \sim 180^\circ$

BLACK	1932733-1
COLOR	PARTS No.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	Tommy Qian	07JUN11		TE Connectivity			
DIMENSIONS: mm		CHK	Martin Li	07JUN11		NAME			
		APVD	Steven Yao	07JUN11		PRODUCT SPEC			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC		108-5983		USB CONNECTOR RECEPTACLE DIP AND OFFSET TYPE			
MATERIAL		FINISH		WEIGHT		SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
1		2		CUSTOMER DRAWING		A3	00779	C=1932733	
				SCALE		SHEET		REV	
				6:1		1 of 2		A	

AMP 1470-19 REV 31MAR2000

