

## Specification Sheet

Part Number: 173-61400



Electromagnetic Protection Braided Sleeving, Flame Retardant, 14 mm Dia,PET;TNCU, TCBK, 328ft/Reel

**Article Number**

173-61400

**Type**

HEGEMIPV014

**Color**

Tin-coloured and Black (TCBK)

**Features & Benefits**

- The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling.
- The special combination of tin-plated copper and PBTVO yarn offers optimal inside and outside abrasion resistance.
- In restricted space areas, HEGMIPV0 is easy to apply without any threads and breaks in the metal.

**Quantity Per**

metre

**Product Description**

HellermannTyton's patented Helagaine HEGEMIP braided sleeving offers electromagnetic protection on highly sensitive electronic applications. This material mix of braided sleeving is self-extinguishing, according to UL94 V0, and is particularly suitable for areas where fire protection is imperative.

<b>Short Description</b>	Electromagnetic Protection Braided Sleeving, Flame Retardant, 14 mm Dia,PET;TNCU, TCBK, 328ft/Reel
<b>Global Part Name</b>	HEGEMIPV014-PBT/TNCU-ML
<b>Length L (Imperial)</b>	328.0
<b>Length L (Metric)</b>	100.0
<b>Bundle Diameter Min (Imperial)</b>	0.47
<b>Bundle Diameter Min (Metric)</b>	12
<b>Bundle Diameter Max (Imperial)</b>	0.71
<b>Bundle Diameter Max (Metric)</b>	18
<b>Diameter D (imperial)</b>	0.55
<b>Diameter D (metric)</b>	14
<b>Nominal Diameter (Imperial)</b>	1/2
<b>Nominal Diameter (Metric)</b>	14
<b>Material</b>	Tin-plated copper (SNCU) Polyester (PBT)
<b>Material Shortcut</b>	TNCU PBT
<b>Flammability</b>	UL 94 V0 FMVSS 302

**Halogen free** No

**Operating Temperature (Metric)** -40°F to +302°F (-40°C to +150°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 328

**Package Quantity (Metric)** 100

**Customs Number** 5902100000

**Content Unit(BMEcat)** metre

**Weight (Imperial)** 11.53